

Uncoated Papers

Water

(eco) Solvent

UV Curable

Latex

IJM043 Recycled White Zero - FSC 80 g/m²

Product Description

Carbon neutral produced high white, smooth recycled paper. No net greenhouse gas (Co2) emissions were used in the paper's entire production process. The paper is made from 100% post-consumer waste.

Physical Properties

Thickness (µm)	106 ± 3	ISO 534	Roughness (ml/min)	220 ± 50	ISO 8791-2 Bendtsen
Weight (g/m ²)	80 ± 3	ISO 536	Brightness UV D65 (%)	104.0 ± 3.0	ISO 2470
Opacity (%)	92.0	ISO 2471	CIE Whiteness	150 ± 3	ISO 11475
Stiffness L&W* (mN)	80 / 45	ISO 2493-1			

*MD/CD

Applications/features

Technical drawings
High white, smooth
Green alternative
Produced Co2 neutral
FSC Recycled certified
EU Eco Label
PCF (Process Chlorine Free)
EN 12281 certified
ISO 14001 certified

Available Widths (mm)

2"core	610	841	914						
--------	-----	-----	-----	--	--	--	--	--	--

Storage Conditions

Temperature 10-20°C, Relative Humidity 20-50%
Repack opened rolls when not in use.

Print Conditions

Best results are obtained between 10-30°C and 40-70% RH.
Refer also to printer specifications.

Environment, Health & Safety

No Material Safety Data Sheet required.

Lamination Compatibility

Cold	Warm	Hot	Cold: pressure sensitive Warm: heat activated: 85°C - 95°C Hot: heat activated: 105°C -130°C
yes	yes	yes	

Outdoor Use

This uncoated paper is not suitable for outdoor use.

Colour Profiles

Canon develops high-quality colour profiles for media / ink / printer / RIP combinations.
Check availability of profiles for your printer on mediaguide.oca.com

Environmental
Certification



Standard disclaimer:

All specifications subject to change without notice. All company and/or product names are trademarks and/or registered trademarks of their respective manufacturers in their markets and/or countries.

Canon Inc.
canon.com
Canon Europe
canon-europe.com
English edition 0615
© Canon Europa N.V., 2016

Canon