

Films

Toner
CrystalPoint
(eco) Solvent
UVgel
Latex

LFM342(L) Roll-up Film 175 µm

Product Description Opaque high-white matt polyester film with a water-fast, low reflecting surface and a metallised light block on the reverse side.

Physical Properties	Thickness (µm)	180 ± 15	DIN EN 20534	Opacity (%)	>99 ± 1	Minolta CR300
	Weight (g/m ²)	240 ± 15	DIN EN ISO 536	Brightness 60° (GE)	5.0 ± 1.5	Zehntner ZGM 1110
	Whiteness (L*a*b)	97.1±1.5;-0.1 ±1.0 -0.1 ± 1.5	Minolta CR300			

Applications/features

- Indoor Signage
- Roll-up displays
- Pop-up displays
- Banner stands
- Excellent image quality
- Dimensionally stable
- Excellent flatness
- Anti-glare matt finish
- Excellent opacity
- Suited for Océ CrystalPoint® Technology

Available Widths (mm)

3"core	914	1270*								
--------	-----	-------	--	--	--	--	--	--	--	--

Refer for our current offering to canon-europe.com/mediaguide
 * marked with L (for Large or Long), rolls weigh upto 30kg

Storage Conditions Shelf life: 1 year. Temperature 20-35°C, Relative Humidity 30-65%
 Repack opened rolls when not in use.

Print Conditions Best results are obtained between 15-25°C and 40-70% RH.
 Refer to printer specifications.

Environment, Health & Safety No Material Safety Data Sheet required.

Lamination Compatibility

Cold	Warm	Hot	Cold: pressure sensitive Warm: heat activated: 85°C - 95°C Hot: heat activated: 105°C -130°C
yes	yes	no	

Outdoor Use Not suited for outdoor use.

Colour Profiles Canon develops high-quality colour profiles for media / ink / printer / RIP combinations.
 Check availability of profiles for your printer on mediaguide.oce.com

**Processing
Guidelines**

Printing guidelines

It is recommended to handle the media with cotton gloves.

Make sure that the media does not come into contact with grease, oil, silicon, and dirt to avoid printing defects.

Print results will vary for different printer/ink combinations.

Canon Colour profiles include recommended ink restrictions and printer parameters. Depending on environment and application, printer parameters may have to be adjusted slightly in order to obtain the best results.

Standard disclaimer:

All specifications subject to change without notice. All company and/or product names are trademarks and/or registered trademarks of their respective manufacturers in their markets and/or countries.