

CrystalPoint

Water

(eco) Solvent

UV Curable

Latex

Uncoated Papers

LFM361 Self-adhesive Paper

90 g/m²

Product Description

Light embossed white self-adhesive paper with a removable rubber-based adhesive and a bleached kraft paper release liner. The paper is matt wood free

Physical Properties

Thickness paper (µm)	122	ISO 534	Peel adhesion 90° (N/25mm)	2.5	FINAT n °2 Stainless steel
Weight (excl. liner) (g/m ²)	90	ISO 536	Initial Tack (N/25mm)	5	FINAT n °9 Glass
Thickness liner (µm)	76	ISO 534	Min. application temp. (°C)	-20	
Weight liner (g/m ²)	75	ISO 536	Service temperature (°C)	-40/+70	
Thickness total (µm)	212 ±10%	ISO 534			

Applications/features

Self-adhesive posters and signs
 Excellent image quality
 Good wet strength
 Excellent adhesion, repositionable.
 Light embossed matt structure
 Suited for Océ Crystal Point® Technology
 German BfR approval for use in direct contact with dry or moist non fatty food

Available Widths (mm)

3"core 1000
 Refer for our current offering to mediaguide.oce.com

Storage Conditions

Shelf life: 2 years, Temperature 25°C, Relative Humidity 40-50%
 Repack opened rolls when not in use.

Print Conditions

Best results are obtained between 10-30°C and 40-70% RH.

Environment, Health & Safety

No Material Safety Data Sheet required. Waste not suitable for recycling.

Lamination Compatibility

Cold	Warm	Hot	Cold: pressure sensitive Warm: heat activated: 85°C - 95°C Hot: heat activated: 105°C -130°C
yes	no	no	

Outdoor Use

This uncoated paper is not suited for outdoor use.

Colour Profiles

Canon develops high-quality colour profiles for media / ink / printer / RIP combinations.
 Check availability of profiles for your printer on mediaguide.oce.com



Processing Guidelines

Printing guidelines

LFM361 is compatible with ColorWave printers with Océ CrystalPoint® technology. High quality print-modes are recommended for best results.

It is recommended to handle the media with cotton gloves. Make sure that the media does not come into contact with grease, oil, silicon, and dirt to avoid printing defects. Insert media with care in the printers. Incorrect loading can cause skewing or creasing. Allow material to adapt to room conditions for 24 hours before printing. It is recommended to calibrate the printer before printing and to make a test print. Print results will vary for different printers.

Ink/toner restrictions and printer settings have to be set for specific printers to obtain the best results. Canon colour profiles include recommended ink restrictions and printer settings for Canon supported printers.

Application guidelines

The adhesive performance is excellent on a wide variety of substrates, combining good initial tack and adhesion with good removability to a variety of substrates. Application to porous substrates or prolonged exposure to U.V. light may adversely affect clean removability.

The best results - when applying the self-adhesive paper to a surface - are obtained if you wipe out the paper with a 100% felt squeegee.

Standard disclaimer:

All specifications subject to change without notice. All company and/or product names are trademarks and/or registered trademarks of their respective manufacturers in their markets and/or countries.