you can
Canon

# Large Format Media
# Product Information Document

## Premium Glossy Paper 2 – 280g/m² – 2941B

| Product Name | Grammage / (g/m²) | Thickness (µ) | Width / mm | Length / m | Mercury Code (EAN128) | POS Code (EAN 13) | Canon iPF5100 | Canon iPF6100 | Canon iPF6200 | Canon iPF6300 | Canon iPF6400 | Canon iPF6400S/SE | Canon iPF6350 | Canon iPF6450 | Canon iPF6000S | Canon iPF6300S | Canon iPF8100 | Canon iPF8300 | Canon iPF8000S | Canon iPF8300S | Canon iPF8400 | Canon iPF8400S/SE | Canon iPF9100 | Canon iPF9000S | Canon iPF9400 | Canon iPF9400S | Canon iPF510 | Canon iPF610 | Canon iPF605 | Canon iPF650 | Canon iPF655 | Canon iPF710 | Canon iPF720 | Canon iPF750 | Canon iPF755 | Canon iPF760 | Canon iPF765 | Canon iPF810 | Canon iPF815 | Canon iPF820 | Canon iPF825 |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| Premium Glossy Paper 2 | 280 | 290 | 432 | 25 | 2941B022 | 8714574610368 | v | v | v | v | v | v | v | v | v | v | v | v | v | v | v | v | v | v | v | v | v | v | v | v | v | v | v | v | v | v | v | v | v | v | v | v |
| | 280 | 290 | 610 | 25 | 2941B021 | 8714574610351 | | v | v | v | v | v | v | v | v | v | v | v | v | v | v | v | v | v | v | v | | v | v | v | v | v | v | v | v | v | v | v | v | v | v | v |
| | 280 | 290 | 914 | 25 | 2941B023 | 8714574610375 | | | | | | | | | | | v | v | v | v | v | v | v | v | v | v | | | | | | v | v | v | v | v | v | v | v | v | v | v |
| | 280 | 290 | 1067 | 25 | 2941B024 | 8714574610382 | | | | | | | | | | | v | v | v | v | v | v | v | v | v | v | | | | | | | | | | | | v | v | v | v |

**Description:** This heavy weight premium photographic quality inkjet paper is designed for high end photo printing using both dye and pigment inks. It is instant dry to touch and offers excellent image quality. It is compatible with a large range of dye and pigment digital printing systems, and is the most ideal product for users who need top quality photographic reproductions.

**Features:** Extremely quick drying, dye and pigment ink compatible, good colour density, excellent image sharpness, smudge resistant, lamination not necessary, easy handling.

**Applications:** Photography, portraits, posters, graphic art reproductions, exhibition graphics, indoor signage.

**Physical Properties:**

| | | |
|---|---|---|
| Weight | 280 g/m² | ±10 |
| Caliper | 290 µm | ±12 |
| Curl at 23 °C, 50% RH | 0 mm | -20 |
| Gloss (75°) | 67% | ±6 |
| Gloss (20°) | 27% | ±6 |
| Opacity | 96% | ±4 |
| Colour (CIE Lab) D50 /2° | L* 94.5 | ±1.5 |
| | a* -0.1 | ±1.0 |
| | b* -2.2 | ±1.0 |

**Printing :** For optimum results select the best possible print settings.

**Finishing:** To add surface protection from dirt, abrasion and gas-fading, lamination is recommended. Although ink drying is virtually immediate, it is still recommended to allow a waiting time of approximately 3 hours before lamination. In order to prevent moisture ingress and paper splitting, lamination with a 5-6mm encapsulated edge is also recommended. Laminate must be evenly applied to the print in order to avoid curling. Both hot and cold lamination is possible.

**Ideal Storage Conditions:**

Store paper only in original boxes, out of direct sunlight and under normal climatic conditions (23 °C, 50% RH) until ready to use. Allow material to adapt to room conditions before use.
Papers can absorb moisture in humid conditions or lose moisture in low humidity conditions. Highly humid conditions make the ink drying time longer and this could interfere with proper laminate adhesion.

**Shelf Life:**

2 years from shipping date when stored under ideal conditions (see a above )